




Pressalit 300 548
Standard toilet seat incl. hinge in stainless steel

<p>Item number</p> <p>Colour</p> <p>Description</p>	<p>548000-D08999 EAN:5708590281421</p> <p>Pressalit 300 has a round, soft design. Specially developed for Sphinx 300.</p> <p>White</p> <p>PRESSALIT toilet seat with cover, model "Pressalit 300", art. no. 548 made of colour ingrained duroplast with BT8/D08 fixed hinge of stainless steel.</p> <ul style="list-style-type: none"> - centre distance: 155 mm - load - ring seat 240 kg - 10 year guarantee 	   
<p>Design type</p> <p>Designer</p> <p>Design year</p>	<p>Wrap-over</p> <p>Frog Design</p> <p>1987</p>	
<p>Materials</p> <p>Maximum load</p>	<p>TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.</p> <p>BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).</p> <p>DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.</p> <p>MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.</p> <p>Load - ring seat 240 kg</p>	



Pressalit 300 548
Standard toilet seat incl. hinge in stainless steel

Weight	3,149 kg
Carton size	488x388x70 mm
Gross weight	3,549 kg
Colli size	500x400x368 mm
Colli weight	17,745 kg
Qty per colli	5
Colli per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	<p>Pressalit provides a 10-year product warranty on your toilet seat. Pressalit will repair or exchange the toilet seat for the same or another useable model, at Pressalit's discretion, in the event of a material or manufacturing defect in your toilet seat appearing within 10 years of the date of purchase with normal use. This product warranty is conditional upon proof of purchase of the toilet seat.</p> <p>Subject to changes in the product range, technical changes and printing errors.</p>

